

Wi-Fi 7 Dual-Band 2.5G AP – Ultra-Fast 3570 Mbps

PRODUCT OVERVIEW

The AIR-AP660N-BE is a high-performance dual-band 2.5 Gigabit wireless access point designed by AirPro, built on the latest 802.11be (Wi-Fi 7) standard. It delivers a combined maximum wireless throughput of 3570 Mbps, providing exceptional network performance for high-density environments. Operating on both 2.4 GHz and 5 GHz frequency bands, the AP660N supports advanced wireless technologies such as 240MHz Channel Bonding and 4096-QAM modulation, ensuring ultra-high-speed connectivity and enhanced capacity.

- Radio 1 (2.4 GHz):
 - Maximum Access Rate: 688 Mbps
- Radio 2 (5 GHz):
 - Maximum Access Rate: 2882 Mbps



With its cutting-edge features and robust performance, the AIR-AP660N-BE is perfect for enterprise-grade wireless deployments, offering seamless connectivity, high bandwidth, and superior user experience.



802.11be



3570Mbps, (688+2882)
Radio 1 (2.4GHz) + Radio 2 (5GHz)



Concurrent users
up to 240



Internal Antenna



2.5GE 802.3at PoE Input



Cloud Management

KEY FEATURES AND HIGHLIGHTS

Enterprise-class indoor 802.11be Wi-Fi 7 wireless access point:

AP660N-BE supports the 802.11be standard, operates in both 2.4GHz and 5 GHz band, and provides an access bandwidth up to 3570 Mbps. This model is the best choice for middle-level office or company as it can support concurrent users up to 240.

Wireless user management at a fine granularity:-

AP660N-BE can support a maximum of 32 WLANs to implement multi-layer multi-service management of wireless users at a fine granularity. Each WLAN supports access control and uplink/downlink rate limit based on MAC or IP addresses. These WLANs may be bound to virtual local area networks (VLANs).

Flexible installation:

AP660N-BE supports wall mounting, ceiling mounting, T-keel mounting, you can deploy it almost everywhere you want.

Powered by PoE port or external power adapter:

AP660N-BE can be powered by PoE port or external power adapter, input 100~240V AC, output: 48V DC.

Multi-mode: fit, fat, bridge:

AP660N-BE can work in fit, fat and Cloud mode and can flexibly switch between these three modes according to network planning requirements.

AirMatch Technology:

AP660N-BE supports AirMatch technology, an advanced AirPro technology that enables continuous WLAN optimization through intelligent client steering, load balancing, seamless roaming, and real-time network-wide monitoring - without requiring client-side software.

PRODUCT SPECIFICATIONS

Hardware Specifications

Item	AIR-AP660N-BE	
Dimensions (L*W*D) (mm)	210 x 210 x 41	
Memory	512MB	
Flash	144MB	
1/2.5G Base-T port	1	
1/2.5G SFP port	1	
USB 2.0	1	
Console port (RJ-45)	1	
BLE port	1	
Indicator LED	Yes	
Reset button	Yes	
Power supply	802.3af & at and External power adapter (Input: 100~240V AC , Output: 48 V DC)	
Maximum power consumption	<19.7W	
RF port	Built-in 2.4 GHz 3 dBi antenna and 5 GHz 3 dBi antenna	
Working frequency band	802.11b/g/n/ax/be: 2.4 GHz to 2.483 GHz 802.11a/n/ac/ax/be: 5.150GHz to 5.350GHz 5.725GHz to 5.850GHz	
Modulation technology	802.11b : BPSK, QPSK, CCK 802.11a/g/n: BPSK, QPSK, 16-QAM, 64-QAM 802.11ac : BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM 802.11ax : BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM, 1024-QAM 802.11be : BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM, 1024-QAM, 4096-QAM	
Transmit power	2.4G: 19dBm (Per Chain: 16dBm) 5G : 21dBm (Per Chain: 18dBm) (Note : final output power comply with deployment regulation might be different)	
Power adjustment granularity	1 dBm	
Working/Storage temperature	0°C to 40°C -40°C to +70°C	
Working/Storage RH	10% to 95% (non-condensing)	
Protection level	Ip30	
WLAN	Product positioning	Indoor dual-frequency
	Working frequency band	2.4GHz and 5GHz
	Bandwidth performance	3570Mbps, 2.4G:688Mbps, 5G:2882Mbps
	SSID/ Virtual AP (BSSID)	32
	Concurrent user	256
	Number of spatial streams (MU-MIMO)	2.4GHz:2x2, 5GHz:4x4
	Dynamic channel adjustment (DCA)	Yes
	Transmit power control (TPC)	Yes
	Blind area detection and repair	Yes
	SSID hiding	Yes
	RTS/CTS	Yes
	RF environment scanning	Yes
	Hybrid access	Yes
	Restriction on the number of access users	Yes
	Link integrity check	Yes
	Accessing control of terminals based on signal strength	Yes
	Forcing terminals to roam based on signal strength	Yes
Intelligent control of terminals based on airtime fairness	Yes	
High-density application optimization	Yes	
802.11be enhancements	Space streams	2.4GHz:2x2, 5GHz:4x4
	Frequency band	2.4GHz + 5GHz
	240 MHz bundling	Yes
	4096-QAM	Yes
	Frame aggregation (A-MPDU)	Yes
	Frame aggregation (A-MSDU)	Yes
	Maximum likelihood demodulation (MLD)	Yes
	Transmit beamforming (TxBF)	Yes
Maximum ratio combining (MRC)	Yes	
Space-time block coding (STBC)	Yes	
Low-density parity-check code (LDPC)	Yes	

PRODUCT SPECIFICATIONS

Hardware Specifications

Security	Encryption	WPA (TKIP), WPA-PSK, WPA2 (AES) WPA3, WEP(64/128 bits), WPA2/3 Enterprises 802.1x
	802.11i,	Yes
	802.11i authentication	Yes
	Portal authentication	Yes
	WAPI	Yes
	MAC address authentication	Yes
	LDAP authentication	Yes
	PEAP authentication	Yes
	WIDS/WIPS	Yes
	Protection against DoS attacks	Anti-DoS for wireless management packets
	Forwarding security	Frame filtering, white list, static blacklist, and dynamic blacklist
	Isolation	wireless user layer 2 isolation, wireless user isolation based on SSID Isolation capability in case of device intrusion.(The anti-brute force mechanism isolates the device when attempts are made to log-in for administrative purposes.)
	Periodic SSID enabling and disabling	Yes
	Access control of free resources	Yes
	Wireless SAVI	Yes
ACL	Access control of various data packets such as MAC, IPv4, and IPv6 packets Identification, monitoring, and control of devices and users accessing the network through applied security policies using ACLs and MAC authentication.	
Secure access control of APs	MAC authentication, password authentication, or digital certificate authentication between an AP and an AC	
802.11W	Yes, encryption of management frames	
Forwarding	IP address setting	Static IP address configuration or dynamic DHCP address allocation
	IPv6 forwarding	Yes
	IPv6 portal	Yes
	Local forwarding	Yes
	Multicast	IGMP snooping
	Roaming	Yes
	AP switching reference	Signal strength, bit error rate, RSSI, S/N, whether neighboring APs are normally operating, etc.
QoS	WDS	Yes
	WMM	Yes
	Priority mapping	Ethernet port 802.1P identification and marking Mapping from wireless priorities to wired priorities
	QoS policy mapping	Mapping of different SSIDs/VLANs to different QoS policies Mapping of data streams that match with different packet fields to different QoS policies
	L2-L4 packet filtering and flow classification	Yes: MAC, IPv4, and IPv6 packets
	Load balancing	Load balancing based on the number of users Load balancing based on user traffic Load balancing based on frequency bands
	Bandwidth limit	Bandwidth limit based on Aps Bandwidth limit based on SSIDs Bandwidth limit based on terminals Bandwidth limit based on specific data streams
	Call admission control (CAC)	CAC based on the number of users
	Power saving mode	Yes
	Automatic emergency mechanism of APs	Yes
Management	Intelligent identification of terminals	Yes
	Multicast enhancement	Multicast to unicast
	Network management	Centralized management through an AC; both fit and fat modes Centralized monitoring and configuration of all devices
	Mesh networking	Yes
	Maintenance mode	Both local and remote maintenance
	Log function	Local logs, Syslog, and log file export
	Alarm	Yes
	Fault detection	Yes
	Statistics	Yes
	Switching between the fat, fit and bridge modes	An AP working in fit mode can switch to the fat mode through a wireless AC; An AP working in fat mode can switch to the fit or bridge mode through a local control port or Telnet(web) An AP working in bridge mode can switch to the fit or fat mode through a local control port or Telnet(web)
Remote probe analysis	Yes	
Watchdog	Yes	



Visit our Website to get Latest Products
and Company Information



Download our Product Guide by
scanning the QR code

Canada Office

AIRPRO NETWORKS
North York, Toronto, Canada, M2J1M6
E-mail: sales@airpronetworks.com
www.airpronetworks.com

India Office

AIRPRO TECHNOLOGY (I) PVT. LTD.
C-53, 3rd floor, Pravasi Industrial Estate, Off Aarey Road,
Vishweshwar Nagar Road, Goregaon East, Mumbai 400 063
E-mail: sales@airpronetworks.com
www.airpronetworks.com

UAE Office

AIRPRO FZ-LLC,
CWEP0213, Compass Building, Al Shohada Road,
AL Hamra Industrial Zone-FZ, Ras Al Khaimah,
United Arab Emirates
E-mail: sales@airpro.ae
www.airpro.ae

Vietnam Office

4th Floor, No. 97, 37th Street, Van Phuc
Urban Area, Hiep Binh Ward, Ho Chi
Minh City, Vietnam

Singapore Office

AIRPRO TECHNOLOGY PTE. LTD. (202444757D)
628 JURONG WEST STREET
65, #16-398, SINGAPORE (640628)
E-mail: sales@airpronetworks.com.sg

Thailand Office

425/1 Enco Terminal Building B, 4th Floor,
Kamphaeng Phet 6 Road, Don Mueang District,
Don Mueang Subdistrict,
Bangkok Thailand 10210



www.airpronetworks.com

All specifications in this document are subject to change without notice. AirPro products are sold with a limited warranty described at: www.airpronetworks.com
Copyright 2024-2026, AirPro. All rights reserved.