

# L3 10G Copper Routing Switch

## PRODUCT OVERVIEW

AirPro AP-SG5550 series are the next generation of enterprise-class stackable routing switches with fixed, built-in 10GbE uplink ports and ship with one power supply. These fully managed switches provide high availability, scalability, security, energy efficiency, and ease of operation with innovative features such as VSF, IEEE 802.3at optional. It is ideal for aggregation or access layer as its high performance, availability and reliability.



## MAIN FEATURES

- 24 x 10/100/1000BaseT + 4 x 10GE(SFP+).
- 1 console, 1 USB, 1 reset, 1 RJ45 management port.
- AC power supply.
- Switching capacity: 128Gbps.
- Forwarding rate: 95Mbps.

## KEY FEATURES AND HIGHLIGHTS

### Performance and Scalability

With high switching capacity, AP-SG5550 series support wire-speed L2/L3 forwarding and high routing performance for IPv4 and IPv6 protocols. The 10 Gigabit Ethernet connectivity of AP-SG5550 is accomplished via a hot-pluggable 10 Gigabit SFP+ transceiver which supports distance up to 300 meters over multimode fiber and 10 to 40km over single-mode fiber (The distance depends the optical module chosen).

### VSF (Virtual Switch Framework)

Virtual Switch Framework can virtualize multiple AirPro switches into one logical device, achieving the sharing of information and data tables between different switches. The performance and ports density of virtualized device are greatly enlarged by times under VSF. VSF also simplifies management work for network administrator and provides more reliability.

### Rich L3 Features

AP-SG5550 series delivers high-performance, hardware based IP routing. RIP, OSPF and BGP provide dynamic routing by exchanging routing information with other Layer 3 switches and routers. With AP-SG5550 series, customers could easily achieve Policy based Route (PBR), which is important when they need multi exit application.

### Strong Multicast

AP-SG5550 series supports abundant multicast features. In Layer 2, such as IGMPv1/v2/v3 snooping and fast leave. L3 multicast

protocols such as IGMPv1/v2/v3. With Multicast VLAN Register (MVR), multicast receiver/sender control and illegal multicast source detect functions; AP-SG5550 series provides great application experience for customer.

### Easy High Reliability network

MRPP is Multi-layer Ring Protection Protocol, which is AirPro's private fast Ethernet ring protocol. Comparing to spanning tree protocol, it has advantages of fast convergence, simple protocol calculation, less system resources cost and so on, which can improve the reliability of Ethernet network operation. Comprehensive QoS With 8 queues per port, AP-SG5550 series enable differentiated management of up to 8 traffic types. The traffic is prioritized according to IEEE802.1p, DSCP, IP precedence and TCP/UDP port number, giving optimal performance to real-time applications such as voice and video. AP-SG5550 series also supports Bi-directional rate-limiting, per port or traffic class, preserves network bandwidth and allows full control of network resources.

### Abundant Ipv6 Support

AP-SG5550 series supports IPv6 switching and routing based on hardware for maximum performance. With increased network devices growing the need for larger addressing and higher security become critical, AP-SG5550 series will be a right product to meet this requirement.

## PRODUCT SPECIFICATIONS

### Hardware Specifications

Item	AP-SG5550 Series	
Physical port	24 x 10/100/1000BaseT + 4 x 10GE(SFP+) Auto-MIDX	
Management port	1 x RJ45 Ethernet Management port 1 x Console port 1 x Reset port 1 x USB2.0 interface	
<b>Performance</b>		
Switching Capacity	4M	
Forwarding rate	95Mbps	
Jumbo Frame	10K	
MAC Address	16K	
ARP Table	4K	
Routing Table	1K	
ACL Table	1K	
<b>Physical</b>		
Dimension (W*H*D)	440mm x 44mm x 240mm	
Relative Humidity	10%~90% non-condensing, storage 95%	
Temperature	Working 0°C~50°C, storage -40°C~70°C	
Power Supply	AC:100~240VAC, 50~60Hz	
Power Consumption	<30W	
<b>Main Features</b>		
L1, L2 Features	IEEE802.3(10Base-T), IEEE802.3u(100Base-TX), IEEE802.3z(1000BASE-X), IEEE802.3ab(1000Base-T), IEEE802.3ae(10GBase), IEEE802.3x, IEEE802.3ak(10GBASE-CX4)	
	Port loopback detection LLDP and LLDP-MED ULDP 802.3ad LACP, max 128 group trunks with max 8 ports for each trunk support max 64 group trunks with max 8 ports for each trunk) LACP load balance ERPS(G.8032) N:1 Port Mirroring RSPAN	
	IEEE802.1d(STP) IEEE802.1w(RSTP) IEEE802.1s(MSTP) Root Guard BPDU Guard BPDU Tunnel	
	802.1Q, 4K VLAN MAC VLAN, Voice VLAN, PVLAN, Protocol VLAN, Multicast VLAN QinQ, Flexible QinQ GVRP N:1 VLAN Translation Broadcast / Multicast / Unicast Storm Control	
	IGMP v1/v2/v3 Snooping and L2 Query ND Snooping MLDv1/v2 Snooping	
	Port Security Flow Control: HOL, IEEE802.3x Bandwidth Control	
	L3 Features	Static Routing, RIPv1/v2, OSPFv2, BGP4 OSPFv3, BGP4+ OSPF multiple process LPM Routing Policy-based Routing(PBR) for IPv4 and IPv6 VRRP URPF, ECMP BFD
		IGMP v1/v2/v3, IGMP Proxy, Static Multicast Route Multicast Receive Control Illegal Multicast Source Detect
		ARP Guard, Local ARP proxy, Proxy ARP, ARP Binding, Gratuitous ARP, ARP Limit Anti ARP Cheat, Anti ARP Scan DNS Client, DNS Relay

## PRODUCT SPECIFICATIONS

### Hardware Specifications

Item	AP-SG5550 Series
Ipv6	6to4 Tunnel, Configured Tunnel, ISATAP Tunnel, ICMPv6,ND,DNSv6 IPv6 LPM Routing,IPv6 Policy-based Routing(PBR) IPv6 VRRPv3,IPv6 URPF,IPv6 RA RIPng,OSPFv3,BGP4+ MLD Snooping,IPv6 Multicast VLAN MLDv1/v2, IPv6 ACL, IPv6 QoS
QoS	8 Queues SP, WDRR, SWDRR Traffic Classification Based on 802.1p COS, ToS, DiffServ DSCP, ACL, port number Traffic Policing PRI Mark/Remark
ACL	IP ACL ,MAC ACL,IP-MAC ACL Standard and Expanded ACL Based on source/destination IP or MAC, IP Protocol, TCP/UDP port, DSCP, ToS, IP Precedence), VLAN, Tag/Untag, CoS Redirect and statistics Rules can be configured to port, VLAN, VLAN routing interfaces Time Ranged ACL
Security	802.1x AAA Port, MAC based authentication Accounting based on time length and traffic Guest VLAN and auto VLAN RADIUS for IPv4 and Ipv6 TACACS+ for IPv4 and Ipv6 MAB
DHCPv4/v6 Traffic Monitor	DHCP Server/Client for IPv4/IPv6 DHCP Relay/Option 82 DHCP Snooping/Option 82
Traffic Monitor	r sFlow Traffic Analysis
Security Network Management	CLI, WEB, Telnet, SNMPv1/v2c/v3 through IPv4 and IPv6 Syslog and external Syslog Server HTTP SSL SNMP MIB, SNMP TRAP FTP/TFTP SNTP/NTP RMOM 1,2,3,9 Authentication by Radius/TACACS SSH v1/v2 Dual firmware images/ Configuration files 802.3ah OAM, 802.1ag OAM
Data Center Features	VSF(Virtual Switch Framework)



[www.airpro.in](http://www.airpro.in)