

8GE+2SFP Ports 48V L2 Managed PoE Switch with 8-Port PoE

PRODUCT OVERVIEW

AirPro 8 Gigabit L2 managed switch provides 8 10/100/1000Mbps ports. The switch provides high performance, enterprise-level QoS, advanced security strategies and rich layer 2 management features. In addition, the switch also comes equipped with 2 gigabit SFP slots, expanding your network flexibly. AP-ESG3010P is cost-effective network solution for the SMB.

AP-ESG3010P includes robust security and management features. The IP-MAC-Port-VID Binding and Access Control List (ACL) functions protect against broadcast storms, ARP, Denial-of-Service (DoS) attacks and so on. Quality of Service (QoS, L2 to L4) provides enhanced traffic management capabilities to move your data smoother and faster. Additionally, the easy-to-use web management interfaces, along with CLI, SNMP, mean faster setup and configuration with less downtime. For workgroup and departments requiring cost-sensitive Layer 2 Switch and gigabit capability, our L2 managed Switch provides you the perfect access-edge solution.



MAIN FEATURES

- 8GE+2SFP Full Gigabit Switch with 8 PoE.
- Internal power adapter supply 125W.
- QoS and IGMP snooping optimize voice and video application.
- Support STP/RSTP.
- Up to 4K QVLANS simultaneously.
- Switching Capacity 20Gbps.
- Packet Forwarding Rate 14.9Mbps.
- 8K Mac address.
- Link Aggregation Control Protocol (LACP).
- WEB/CLI managed modes, SNMP, bring abundant management features.

KEY FEATURES AND HIGHLIGHTS

SECURE NETWORKING

AP-ESG3010P consists of IP-MAC-Port-VID Binding, Port Security, Storm control and DHCP Snooping which protect against broadcast storms, ARP attacks, etc. It integrates some typical DoS attacks to select. You can protect these attacks more easily ever than before. Moreover, Access Control Lists (ACL, L2 to L4) feature restricts access to sensitive network resources by denying packets based on source and destination MAC address, IP address, TCP/UDP ports and even VLAN ID. Also, the switch supports 802.1X authentication, which is used in conjunction with a RADIUS server to require some authentication information before access to the network is allowed.

ADVANCED QOS FEATURES

AP-ESG3010P has the built-in Portal Server and user accounts, so it doesn't need an external Portal Server and Radius Server to do the WEB authentication, resulting in both simplified network deployment and reduced network construction cost. To integrate

voice, data and video service on one network, AirPro 8 Gigabit L2 managed switch features rich QoS policies. The administrator can designate the priority of the traffic based on a variety of means, including IP or MAC address, TCP or UDP port number, etc., to assure that voice and video are always clear, smooth and jitter free.

ADVANCED QOS FEATURES

AP-ESG3010P supports a complete lineup of layer 2 features, including 802.1Q tag VLAN, Port Isolation, Port Mirroring, STP/RSTP, Link Aggregation Control Protocol and 802.3x Flow Control function. Also, the switch provides advanced features for network maintenance such as Loop Back Detection, Cable Diagnostics and IGMP Snooping. IGMP snooping ensures that switch intelligently forward the multicast stream only to the appropriate subscribers while IGMP throttling & filtering restrict each subscriber on a port level to prevent unauthorized multicast access.

PRODUCT SPECIFICATIONS

Hardware Specifications

Item	AP-ESG3010P
Interface	8 10/100/1000Mbps RJ45 Ports (Auto Negotiation/Auto MDI/MDIX) 2 1000Mbps SFP Slots 1 Console Port
Network Media	10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) 100BASE-TX/1000Base-T: UTP category 5, 5e, 6 or above cable (maximum 100m) 1000BASE-X: MMF, SMF 1000Base-L X:62.5µm/50µm MM(2m~550m) or 10µm SMF(2m~5000m)
Fan Quantity	Fanless
Power Consumption	125W (max. with PoE device connected)
External Power Supply	AC 110~265V 50/60HZ
PoE Ports (Rj45)	Standard: 802.3 af/at compliant PoE Ports: Port1- Port8 Power Supply: 125W
Switching Capacity	20Gbps
Packet Forwarding Rate	14.9Mpps
Mac Address Table	8K
Packet Buffer Memory	4Mb
Jumbo Frame	10240 Bytes
Dimensions	Product Size: 225mm* 105mm*32mm(L*W*H)
Quality of Service	Support 802.1p CoS/DSCP priority Support 4 priority queues Queue scheduling: SP, WRR, SP+WRR Port/Flow- based Rate Limiting
L2 Features	IGMP Snooping V1/V2/V3 802.3ad LACP (Up to 8 aggregation groups, containing 8 ports per group) Spanning Tree STP/RSTP/MSTP Port isolation BPDU ltering/guard TC/Root protect Loop back detection 802.3x Flow Control
VLAN	Supports up to 4K VLANs simultaneously (out of 4K VLAN IDs) Port/ MAC/Protocol-based VLAN Management VLAN conguration
Access Control List	L2~L4 package ltering based on source and destination MAC address, IP address, TCP/UDP ports, 802.1p, DSCP, protocol and VLAN ID; Time Range Based
Security	IP-MAC-Port-VID Binding IEEE 802.1X Port/MAC Based authentication, Radius,Guest VLAN DoS Defence, Dynamic ARP inspection (DAI) SSH v1/v2, SSL v2/v3/TLSv1 Port Security, Broadcast/Multicast/Unknown-unicast Storm Control
Management	Web-based GUI and CLI management SNMP v1/v2c/v3,compatible with public MIBs DHCP/BOOTP Client, DHCP Snooping, CPU Monitoring, Port Mirroring Time Setting: SNTP Integrated NDP/NTDP feature Firmware Upgrade: TFTP & Web System Diagnose: VCT SYSLOG & Public MIBS

PRODUCT SPECIFICATIONS

Hardware Specifications

Item	AP-ESG3010P
Certification	CE, FCC, RoHS
Package Content	PoE Switch Power Cable Guide Book/Warranty Card
Environment	Working Temperature: 0°C~40°C Storage temperature : -40°C~70°C Working Humidity : 10%~90% RH non-condensing Storage Humidity: 5%~90% RH non-condensing



www.airpro.in