

6 Ports Gigabit Managed Industrial PoE Switch

PRODUCT OVERVIEW

6-port Gigabit Industrial Ethernet PoE Switch, 4 Gigabit PoE Ports + 2 Gigabit SFP Port + 1 Console port, supporting Din rail and wall mounting. Supports dual power input (DC48-55V), -40 to 75°C working temperature; Certified by industrial environment and support FCC, CE, CCC, RoHS standards; Reliable industrial design ensures uninterrupted automation system Stable operation.

This series of industrial grade switches can be widely used in wind power, electric power, assembly automation, subway PIS, electric power SCADA, sewage treatment, metallurgy, intelligent transportation, rail transportation, military and other industries. It is a green low-power industrial Ethernet switch.

This series of switches provides advanced network management capabilities: redundant ring, loop protection, VLAN, QOS, speed control, port mirroring, and firmware online upgrades. With standardized industrial design, it can meet the stringent requirements of industrial sites. All components use industrial grade for greater reliability, providing redundant, wide-voltage power inputs and outputs for uninterrupted industrial safety communications.



MAIN FEATURES

- Support IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3z / ab, IEEE802.1Q, IEEE802.1p, IEEE802.1d/w.
- PoE Power Management, PoE Watchdog based on data stream detection.
- Support IEEE802.3af (15.4w), IEEE802.3at (30W).
- Support STP (802.1D), RSTP (802.1w), MSTP (802.1s), ERPS.
- Support SNMP v1/v2/v3.
- Support IGMP Snooping, Static multicast filtering and MLD Snooping.
- Support 802.1x port and AAA Certification, Enhance network security.
- Support WEB, Telnet, CLI, SSH management.
- IP40 protection, rugged high-strength metal case, DIN35 Rail mounting.
- EMC grade 4 design, -40 to 75°C working temperature.
- Support Redundant power supply access, support anti-reverse connection.
- Surge Protection: General 6KV, Differential 4KV; ESD 15KV(Air), 8KV (Contact)
- Support EMC EN55032 standard.

APPLICATION SITUATIONS:

- Metropolitan area fiber broadband network: telecommunications, cable TV, network system integration, etc., network operators.
- Broadband private network: Suitable for financial, government, oil, railway, electric power, public security, transportation, education and other industries.
- Multimedia transmission: image, voice, data integrated transmission, suitable for remote teaching, conference TV, videophone and other applications.
- Real-time monitoring: simultaneous transmission of real-time control signals, images, data.
- Resistant to harsh environment: Suitable for strong electromagnetic interference, networking in harsh environments at long distances.

PRODUCT SPECIFICATIONS

Hardware Specifications

Item	AP-IGS9006P										
Product Name	6 Ports Gigabit Managed Industrial PoE Switch										
Port Definition	4 Gigabit PoE Ports + 2 Gigabit SFP Port + 1 Console port										
Network Protocols	IEEE802.3 IEEE802.3u IEEE802.3z IEEE802.3ab IEEE802.3x IEEE802.1d IEEE802.1w										
PoE Parameters	PoE Standard: IEEE 802.3af / IEEE 802.3at Single PoE Port Power Output: Max: 15.4 W (IEEE 802.3af) Max: 30 W (IEEE 802.3at) PoE Compatibility: IEEE 802.3af / at adaptive POE Power Output: DC 48-55V POE Power Pin: 1/2- ; 3/6+										
Network Media	10BASE-T: Cat 3, 4, 5 UTP (≤100 M) 100BASE-TX: Cat5 or above UTP (≤100 M) 1000BASE-TX: Cat5 or above UTP (≤100 M)										
Fiber Media	Multi-mode: 850nm, 1310nm Transmission Distance: 550m/2Km Single-mode: 1310nm, 1550nm Transmission Distance: 20/40/60/80/100/120Km										
LED Indicator	<table border="0"> <tr> <td>PWR</td> <td>Lighting: Powered Un-Light: No Power</td> </tr> <tr> <td>SYS</td> <td>Lighting: System is operating normally Un-Light: System is not running</td> </tr> <tr> <td>Yellow light</td> <td>Lighting: PoE Powered Un-Light: No PoE Powered</td> </tr> <tr> <td>Green light</td> <td>Slow Flashing: 10/100/1000 Link normally Un-Light: Link disconnect Flashing: Link data transmission</td> </tr> <tr> <td>G5-G6</td> <td>Lighting: Fiber Connection is Normal Un-Light: Disconnect Flashing: Link data transmission</td> </tr> </table>	PWR	Lighting: Powered Un-Light: No Power	SYS	Lighting: System is operating normally Un-Light: System is not running	Yellow light	Lighting: PoE Powered Un-Light: No PoE Powered	Green light	Slow Flashing: 10/100/1000 Link normally Un-Light: Link disconnect Flashing: Link data transmission	G5-G6	Lighting: Fiber Connection is Normal Un-Light: Disconnect Flashing: Link data transmission
PWR	Lighting: Powered Un-Light: No Power										
SYS	Lighting: System is operating normally Un-Light: System is not running										
Yellow light	Lighting: PoE Powered Un-Light: No PoE Powered										
Green light	Slow Flashing: 10/100/1000 Link normally Un-Light: Link disconnect Flashing: Link data transmission										
G5-G6	Lighting: Fiber Connection is Normal Un-Light: Disconnect Flashing: Link data transmission										
Power Supply	Input Voltage: DC-4855V Type of input: 4 PIN Industrial Terminal (block V1+V1- V2+ V2-)										
Physical structure	Protect grade: IP40 Installation: DIN Rail Product weight: 0.6KG Package weight : 0.8 KG (Without power) Product Dimensions (L×W×H): 145mm×108mm×40 mm Package Dimensions (L×W×H): 245mm×190mm×60mm Standard packing(L×W×H): 520mm× 320 mm× 400mm Standard packing quantity: 20 (PCS)										
Working Environment	Operating temperature: -40 ~ 75°C Storage temperature: -40 ~ 85°C Humidity: 5% ~ 95 % (No condensation)										
Industry Standard	EMI: FCC Part 15, CISPR (EN55032) class A EMS: EN61000-4-2 (ESD) EN61000-4-4 (EFT) EN61000-4-5 (Surge)										
Certification	CE, FCC, ROHS										
MTBF	100,000 hours										
Packing list	1. Industrial grade switch: 1 Set 2. Instruction manual: 1 PCS 3. Certificate, warranty card: 1 PCS 4. Serial cable: 1PCS										
Warranty	5 years										

PRODUCT SPECIFICATIONS

Hardware Specifications

Item	AP-IGS9006P
Hardware Parameters	
Bandwidth	12Gbps
Packet Forwarding Rate	8.928Mpps
RAM	128MB
Flash	16MB
Packet Buffer Memory	4M
Jumbo frame	9.6Kbytes
VLANs	4096
MAC	8K
Forwarding Mode	Store-And-Forward
L3 Function	
IPv4	IPv4 VLAN Interface IPv4 Static Routes ARP
L2 Function	
Port	Port Switch Port Description Port Speed Port Duplex Port Flow Control Jumbo, up to 9600bytes EEE Fiber Module (DDM)
Link Aggregation	Supports load balance policy; Base on SMAC/DMAC/IP and TCP/UDP port number Static and Dynamic Group Supports LACP
Storm Control	Broadcast Unknown Multicast Unknown Unicast
Port Mirroring	One to one monitor Many to one monitor Ingress/Egress/Both
Port Security	MAC Address Constraints Action: Trap/Shutdown Port Isolation, Port Rate-limit, Loopback Detection
VLAN	Access/Trunk/Hybrid VLAN Tunnel (Q-in-Q Tunnel) Configurable VID from 1 - 4094; Max. 4K static VLAN groups GVRP
MAC Address	Dynamic Address Static Address
Spanning Tree Protocol	STP/RSTP/MSTP BPDU Filter BPDU Guard Edge Port
ERPS	Major and sub ring up to 16 rings
Multicast	IGMP Snooping IGMP V1/V2/V3 Router Port Static IGMP group address IGMP groups filtering Querier MLD Snooping
QoS	Traffic classification based, Strict priority and SP+WRR Port Priority 802.1P Priority IP DSCP Priority Supports up to 8 queues per port Port Shaping

PRODUCT SPECIFICATIONS

Hardware Specifications

<i>Item</i>	<i>AP-IGS9006P</i>
PoE	
PoE Configuration	<ul style="list-style-type: none"> PoE Temperature PoE Type/Level/Power/Current PoE Switch PoE Watchdog Total PoE power budget control PoE power management PoE port priority Per PoE port power limit, PoE Schedule PoE Port Timer Reboot
Services	
DHCP	<ul style="list-style-type: none"> DHCP Server IP Pool Static Binding DHCP Relay
Access Protocol	<ul style="list-style-type: none"> HTTP Telnet SSH Manager ACL
Security	
AAA	<ul style="list-style-type: none"> RADIUS TACACS+ 802.1X Base on port/MAC authentication DHCP Snooping IP Source Guard Dynamic ARP Inspection Port ACL
ACL	<ul style="list-style-type: none"> MAC ACL IPv4 ACL IPv6 ACL Permission level management
Diagnostics	
Syslog	<ul style="list-style-type: none"> Logging Message Remote Server Ping Traceroute Cable Diagnostics
Management	
Manager Access	<ul style="list-style-type: none"> Console HTTP Telnet SSHv2 SNMP
Manager IP	<ul style="list-style-type: none"> Static Address DHCP Client Supports IPv4 and IPv6 address DNS
Time Synchronization	<ul style="list-style-type: none"> SNTP Manual Time
SNMP	<ul style="list-style-type: none"> V1/V2C/V3 Community V3 User Group Trap Host
SNMP MIB	<ul style="list-style-type: none"> RFC 1213 MIB-II RFC 1493 Bridge MIB RFC 1643 Ethernet MIB RFC 2863 Interface MIB Private MIB

PRODUCT SPECIFICATIONS

Hardware Specifications

Item	AP-IGS9006P
User	Configurable user privilege level from 0 - 15;
Firmware	Double Image; Swap between Active and Alternate firmware image. Firmware update
Configuration	Upload and download Save Restart Factory Defaults
Standards Compliance	IEEE 802.3x flow control and back pressure IEEE 802.3ad port trunk with LACP IEEE 802.1D Spanning Tree Protocol IEEE 802.1w Rapid Spanning Tree Protocol IEEE 802.1s Multiple Spanning Tree Protocol IEEE 802.1p Class of Service IEEE 802.1Q VLAN tagging IEEE 802.1x Port Authentication Network Control IEEE 802.1ab LLDP IEEE 802.3af Power over Ethernet IEEE 802.3at Power over Ethernet Plus RFC 768 UDP RFC 793 TFTP RFC 791 IP RFC 792 ICMP RFC 2068 HTTP RFC 1112 IGMP v1 RFC 2236 IGMP v2 RFC 3376 IGMP v3 RFC 2710 MLD v1 RFC 3810 MLD v2 ITU-T G.8032 ERPS Ring

ORDER INFORMATION

Product	Description
AP-IGS9006P	Layer 2 Management, 4 Gigabit PoE Ports + 2 Gigabit SFP Port + 1 Console port



www.airpro.in